

UltraFloc 322HV

Liquid Cationic Polymer

UltraFloc 322HV

Technical Data Sheet

UltraFloc 322HV is a cationic, medium viscosity, high molecular weight Poly-DADMAC. It is effective as a flocculant in raw water/waste water clarification. It is also beneficial as a filter aid in treating raw water/waste water. UltraFloc 322HV is certified to NSF/ANSI Standard 60 up to 50 mg/L in potable water.

P.O. Box 520
 700 Hwy 33 South
 Centreville, MS 39631
 USA
 Tel: (601) 645 6536
 Fax: (601) 645 6633

Please send email enquiries to:
wtc.sales@geosc.com

Website: www.geosc.com

Technical Data	Typical Properties
Appearance	Viscous, Clear, Yellow-colored Liquid
Odor	Slight Amine
Product Viscosity @ 25°C	1,000 – 3,000 cP
Density	8.67 lbs/gal
Flash Point	None
Boiling Point (°C @ 760 mm Hg)	>100°C
Freezing Point (°C)	< 0°C
pH, Neat (as is):	5.0 – 8.0
Shelf Life:	One Year

Handling, Storage and Feeding

UltraFloc 322HV should be transferred only in well-ventilated areas. As with all chemicals, care should be taken during transfer and appropriate protective equipment should be worn. Clean up spills immediately using inert absorbent materials such as clays, sand, earth or other commercially available dry sweeping compound. The product may cause a slip hazard. Product should be stored in fiberglass, stainless steel or plastic lined vessels located in a cool area. However, avoid storage temperatures below freezing, since this product may stratify. UltraFloc 322HV is shipped in bulk tank trucks, in 55-gallon (208 liters) non-returnable drums, or in 275-gallon / 330-gallon plastic totes. Use corrosion resistant, positive displacement pump to meter the neat product to a water line for continuous dilution to 0.5% or less before application. Feed the diluted product or, in some cases, neat product at a point which ensures complete mixing, such as prior to the rapid mix zone.

This information is true and accurate to the best of our knowledge, but without any guarantee unless explicitly given. Typical properties should not be construed as specifications. Since the conditions of use are beyond our control we disclaim any liability, including for patent infringement, resulting from the use of these product, data or suggestions.