

Absorbent Clay Concentrates

$$\text{Al}_2\text{Si}_2\text{O}_7$$

Aluminum Silicate

Product Bulletin

9213 Arch Street Pike
 Little Rock, AR 72206
 USA
 Tel: +1 501 888 1211
 Toll Free 800 453 2586

Please send email enquiries to:
wtc.sales@geosc.com

Website: www.geosc.com

Absorbent Clay Concentrates is a fired Kaolin granular material that varies in appearance from gray to dark green.

The product is primarily Meta-Kaolin and contains amorphous silica.

Specifications	
CAS Number	66402-68-4
CAS Index Name	Ceramic Materials and Wares, Chemicals
Grade	Technical
Molecular Weight	222.13
Al ₂ O ₃ :	37.0% minimum
Fe ₂ O ₃ :	2.0% maximum
Loss on Ignition:	2.0% maximum

Typical Properties	
Bulk Density (pounds per cubic foot):	50-55
Granular Size (U.S. Standard):	-8 +60
Flash Point:	Noncombustible

Note: Depending on requirements, granular size and distribution can be tailored to meet specific process needs.

Uses

Industrial: Spills and cleanup.

Incineration: Absorbent for liquid waste.

Metallurgy: Cutting and abrasion.

Ceramic and Refractory Industries

Containers:

- ◆ 100-Ton net weight Bulk Cars
- ◆ 25-Ton net weight Bulk Trucks
- ◆ 2000-Pound net weight Super Sacks

This information is true and accurate to the best of our knowledge, but without any guarantee unless explicitly given. Typical properties should not be construed as specifications. Since the conditions of use are beyond our control we disclaim any liability, including for patent infringement, resulting from the use of these product, data or suggestions.