

# UltraFloc 320LV

## Liquid Cationic Polymer

UltraFloc 320LV

Technical Data Sheet

UltraFloc 320LV is a cationic, medium viscosity, high molecular weight Poly-DADMAC. It is effective as a flocculent in raw water/waste water clarification. It is also beneficial as a filter aid in treating raw water/waste water. UltraFloc 320LV is certified to NSF/ANSI Standard 60 up to 26 mg/L in potable water.

P.O. Box 520  
 700 Hwy 33 South  
 Centreville, MS 39631  
 USA  
 Tel: (601) 645 6536  
 Fax: (601) 645 6633

Please send email enquiries to:  
[wtc.sales@geosc.com](mailto:wtc.sales@geosc.com)

Website: [www.geosc.com](http://www.geosc.com)

Technical Data	Typical Properties
Appearance	Viscous, Clear, Yellow-colored Liquid
Odor	Slight Amine
Product Viscosity @ 25°C	1,000 – 3,000 cP
Density	9.00 lbs/gal
Flash Point	None
Boiling Point (°C @ 760 mm Hg)	>100°C
Freezing Point (°C)	< 0°C
pH, Neat (as is):	5.0 – 8.0
Shelf Life:	One Year

## Handling, Storage and Feeding

UltraFloc 320LV should be transferred only in well-ventilated areas. As with all chemicals, care should be taken during transfer and appropriate protective equipment should be worn. Clean up spills immediately using inert absorbent materials such as clays, sand, earth or other commercially available dry sweeping compound. The product may cause a slip hazard. Product should be stored in fiberglass, stainless steel or plastic lined vessels located in a cool area. However, avoid storage temperatures below freezing, since this product may stratify. UltraFloc 320LV is shipped in bulk tank trucks, in 55-gallon (208 liters) non-returnable drums, or in 275-gallon / 330-gallon plastic totes. Use corrosion resistant, positive displacement pump to meter the neat product to a water line for continuous dilution to 0.5% or less before application. Feed the diluted product or, in some cases, neat product at a point which ensures complete mixing, such as prior to the rapid mix zone.

This information is true and accurate to the best of our knowledge, but without any guarantee unless explicitly given. Typical properties should not be construed as specifications. Since the conditions of use are beyond our control we disclaim any liability, including for patent infringement, resulting from the use of these product, data or suggestions.