

# UltraPAC 524LF

## Liquid Cationic Melamine Resin

### UltraPAC 524LF

### Technical Data Sheet

UltraPAC 524LF is a cationic, low molecular weight Melamine Resin with low Free Formaldehyde (less than 0.1%). It is effective for oil and water separation in refinery flotation units. It is also used for latex waste clarification and textile industry waste in conjunction with an anionic polymer. UltraPAC 524LF is effective in paint detackification, as in new car paint booths or anywhere paint is applied. GEO Specialty Chemicals holds the patent for this product.

P.O. Box 520  
 700 Hwy 33 South  
 Centreville, MS 39631  
 USA  
 Tel: (601) 645 6536  
 Fax: (601) 645 6633

Please send email enquiries to:  
[wtc.sales@geosc.com](mailto:wtc.sales@geosc.com)

Website: [www.geosc.com](http://www.geosc.com)

Technical Data	Typical Properties
Appearance	Clear, Yellow Green Liquid
Odor	Organic Amine
Product Viscosity @ 25°C	<20 cps
Density	8.55 lbs/gal
Flash Point	None
Boiling Point (°C @ 760 mm Hg)	>100°C
Freezing Point (°C)	< 0°C
pH, Neat (as is), @ 25°C	1.1 - 2.0
Shelf Life:	Six Months

## Handling, Storage and Feeding

UltraPAC 524LF should be transferred only in well-ventilated areas. As with all chemicals, care should be taken during transfer and appropriate protective equipment should be worn. Clean up spills immediately using inert absorbent materials such as clays, sand, earth or other commercially available dry sweeping compound. Store it in fiberglass, stainless steel or plastic lined vessels located in a cool area. However, avoid storage temperatures below freezing, since this product may stratify or gel. Avoid mixing the neat material with other dissimilar polymers since the product may gel. UltraPAC 524LF is shipped either in bulk, in 55-gallon (208 liters) non-returnable drums, or in 275-gallon / 330-gallon plastic totes. Use corrosion resistant pipes and corrosion resistant positive displacement pumps when handling the product for its application(s).

This information is true and accurate to the best of our knowledge, but without any guarantee unless explicitly given. Typical properties should not be construed as specifications. Since the conditions of use are beyond our control we disclaim any liability, including for patent infringement, resulting from the use of these product, data or suggestions.